


H3R说明书尺寸：65*90mm
正反16面 7折 英文朝上

[illegible]




Carbon HI

High Brightness Long-range Search Flashlight

User Manual

Specifications		Discharging Curve					
OUTPUT (Beam)	ECO	LOW	MED	HIGH	TURBO	STROBE	SOS
MAXIMUM BRIGHTNESS	150	150	600	600	4000	10	10
BEAM DISTANCE	950	1300	55	12	4	8	10
BEAM DURATION	50	125	250	360	100	/	/
INTENSITY (Candela)	425	2906	16425	78400	303000	/	/
IMPACT RESISTANCE	1 meters						
WATER RESISTANCE IPX8 (20 meters underwater)							
SIZE 205mm/6.9in x 4.5mm							
WEIGHT 36g (excluding battery)							
WORKING TEMPERATURE -30°C/-22°F ~ 55°C/131°F							
STORAGE TEMPERATURE -30°C/-22°F ~ 40°C/104°F							
OPERATING VOLTAGE RANGE 2.5V ~ 3.6V							
BATTERY COMPATIBILITY This product comes compatible with the BL3635 battery or other batteries can be used.							

Note: The data above is based on the ANSI / ILLUMINANCE PLATO P1 standard. The flashlight is tested in a laboratory environment at 23°C±2°C and 50%±5% humidity, tested in the laboratory environment. Actual performance may vary with battery and usage conditions. The overall endurance time refers to the total duration of the smart dimming.



38121 1500mAh Lithium Ion Phosphate Battery

LOW: 150 hours
MED: 55 hours
HIGH: 12 hours
TURBO: 4 hours
ECO: 950 hours

Operating Instruction

Power On/Off: Single click the button to turn on/off. When power on, it remembers the last used mode only (LOW, MED, HIGH modes).

Adjust Brightness: Long press the button to cycle through LOW > MED > HIGH, release to select brightness.

ECO: Long press the button while the flashlight is off.

TURBO: Double-click to enter TURBO (brightness decreases gradually based on battery voltage and temperature).

STROBE: Triple-click to enter STROBE, click once or long press to exit.

SOS: In STROBE, triple-click to enter SOS, click once or long press to exit.

Lock/Unlock: Fast or more quick clicks to lock/unlock (Low Mode flashes twice to indicate status).

Smartly Reduce Brightness: To increase lighting safety, the product will intelligently reduce the brightness in the following situations:
Automatic brightness reduction to low mode when battery is low.
If the product temperature is higher than the safe value (55°C), the brightness of the product will be reduced through temperature control to avoid product damage and injury to users.

Low Battery Warning:

LED flashes three times every three minutes indicating low battery. Battery needs to be charged or replaced.

Battery Level Indicator

Shows current battery level for 3 seconds when turned on.

100%	●●●●●	Red light blinks
80%-99%	●●●●○	
60%-79%	●●●○●	
40%-59%	●●○●●	
20%-39%	●○○●●	
When battery is below 20%:	○○○○○	

Charging: Insert the charging cable. Green light indicates full charge (about 4 hours to full).

Discharging: LED indicators off from right to left when discharging. Unplug after full charge.

Fast Charge Protocols:

- Support PPS Output
- Support QC2.0 Output
- Support QC3.0/QC3.3 Output
- Support FC01 Output
- Support FC02 Output
- Support FC03 Input/Output
- Support FC04 Input/Output
- Support BL1.2 Functionality

Precautions:

- Different charging protocols support different currents. The voltage platform of the flashlight battery is 3.6V. Charging to external devices stops when the battery voltage drops below 3.0V (about 50% capacity).
- It is recommended to use the matching charging cable for charging/discharging.
- When using a C to A adapter, please choose one with OTG function.
- If other C-C charging cables or adapters cannot charge, try inserting the charging cable in the opposite direction.
- When charging on iPhone, please use the original Apple charging cable.

Caution

- Do not connect battery positive and negative terminals backward.
- Please fully charge the battery before first use.
- Children must use this product under adult supervision.
- Do not put the product with opened cover into water.
- Do not put the product with the battery into the fire. Otherwise, it will be liable.
- The product has high brightness, please do not look directly at the lamp beads, as it may cause eye damage and temporary blindness.
- Please remove the batteries when the product is left unused.
- When carrying, please turn the battery cover loose half a turn to let the product power off to avoid mistakenly lighting up while carrying.
- When using an external power supply to power the Carbon HI lamp head (without the body and battery), the light may jitter or flicker on low settings. This is because the fast dimming technology used in this product is a normal phenomenon.

Warranty Terms

For the first 15 days from the date of sale, if there is a product quality problem under normal use, customers can choose to replace with a new product of the same model and specification. If the product of the same model and specification has been discontinued, it will be replaced with a product of the same brand and class with no lower performance.

1-year free warranty period from the date of sale. The lamp product has a free warranty period of 1 year (1 year for batteries). If there is a product quality problem under normal use, the user can enter free repair service. After 5 years, paid repair service will be provided, only cost fees will be charged.

When consumers seek warranty service, they should contact the dealer with the "Warranty Card", shipping invoice or receipt or the code provided by the online retailer, and the dealer will provide service to the customer. Our company will provide service support to the dealer. Warranty service does not include any damage or malfunction caused by the following reasons:

- Cracking from high altitude, modification or alteration without permission.
- Damage caused by rough or mistaken operation.
- Damage caused by improper use, storage or maintenance.
- Normal wear and tear caused by battery.
- Corrosion of the unit caused by saltwater.
- Ordinary wear fading.

Certifications

CE, FCC, RoHS 2.0, UKCA, sealar safe transport.

Included:

- Carbon HI flashlight, including bag, BL3635 battery, waterproof ring, charging cable, instruction manual, certificate of conformity, inland warranty card.